



*Aladdin*  
PRODUCTS






## Bi-Flexlite

### BI-FLEX LITE 50/200

	AMS-FL50BI	AMS-FL200BI
Light source	High CRI LED	High CRI LED
Power consumption	50W	200W
Beam angle	130°	130°
Color temperature	3000~6000K	3000~6000K
Color rendering Index	T/97ra D/97Ra	T/97ra D/97Ra
Dimming	0~100%	0~100%
IP level	IP67	IP67
Size	300x300mm	300x1200mm
LED module weight	220g	800g
Luminous intensity	3000k 1530LX @1M 6000k 1910LX @1M	3000k 5350LX @1M 6000k 5530LX @1M
Power supply	50W SMPS(NO COOLING FAN) Input voltage:100~240Vac/50,60Hz DC 12~18V	200W SMPS(NO COOLING FAN) Input voltage:100~240Vac/50,60Hz DC 24~30V

# Aladdin

## BI-FLEX



- > Bi-color LED panel satisfies all conditions of broad cast, movie and photo production
- > High color-rendering index over 97Ra
- > Wide-range color temperature (3000K - 6000K)
- > Accommodates portable workflow with V-Lock and Gold Mount battery mounting plates (optional)
- > Bi-color LED panel and cable are constructed from waterproof materials
- > UV 90% cut off

### IN THE BOX



The Aladdin BI-FLEX has several distinctive features that conventional high-power lamps are unable to match. The incredibly thin panel material integrated with a state-of-the-art LED array make the unit significantly lighter and allows for fast and easy set-up and portability. Not only is the splash-proof panel flexible, but it has integrated velcro corners and o-rings, which allow for nearly limitless set-up possibilities.



### ADDITIONAL ACCESSOIRES

- > Softbox
- > Pancake
- > Magnetic holder
- > V-Mount
- > Belt Clip
- > DTAB Cable

AMS-20T/D LED Desklight sports by far superior CRI compared with typical LED lamps. So, the device can be used as both reducing neck shadow or making artificial catchlight.



# LED Desklight

## AMS-20T/D

	3000K	• • • • •	5600K	Others
Light source	Super high CRI LED array (20W)			built-in tilting stand w/1/4" screw hole built-in filter holder option : remote wire switch
Viewing angle	140 ° (80 ° at FWHM both horizontal and vertical)			
Color temp.	3000K ~ 5600K			
CRI	min. 97ra		min. 95ra	
Luminous flux	1,500 lumen			
Luminous intensity	540 lux @ 1m		530 lux @ 1m	
Driver	Flicker-Free by CC driver (efficiency > 93%)			
Control	Dimming : 5% ~ 100%			
Power supply	33W SMPS (No fan)			
	Input voltage : 100 ~ 240VAC (50~60Hz)			
	UL, CE, TUV, PSE, CCC, KC certified			
Battery	BUILT-IN Li-Ion battery (14.8V 2600mAh), 3400mAh optional			
Run Time	2 hrs. by battery (Max. output), continuous drive w/charger			
Housing material	Aluminium 6061 T6 (Aircraft grade) anodized			
Cooling	Air convection cooling			
Dimension	70 x 270mm (30mm Thickness)			
	Weight : 0.8kg			



LED Notelite boasts an integrated color temperature mode with a small package. This light can be neatly attached most DSLRs as well as ENG video cameras.



# LED Notelite

## AMS-08T/D

	3200K	• • • • •	5600K	Others
Light source	Super high CRI Power LED × 112EA (8W)			option parts : diffuser plate  built-in 1/4" screw hole
Beam angle	140 ° (80 ° at FWHM both horizontal and vertical)			
Color temp.	3000K ~ 6000K			
CRI	97ra		95ra	
Luminous flux	600 lumen		650 lumen	
Luminous intensity	240 lx @ 1m		260 lx @ 1m	
Driver	Flicker-Free by CC driver (efficiency > 93%)			
Control	Dimming (5% ~ 100%)			
Battery	3.7V 2.5A Li-Ion battery			
Housing material	Aluminium 6061 T6 (Aircraft grade) Type III black HA and red anodized			
Cooling	Air convection cooling			
Dimension	156 × 80 × 11.5mm Weight : 205g			



control panel



diffuser plate



high quality leather pouch



Accessories



shoulder bag



1/2/4P holder



magnet holder



# LED Eyelite

## AMS-02T, 02D

## AMS-04C

LED Eyelite series, as the name implies, is designed to use small yet useful catchlight device. The versatile one can be used not only as hidden light, but also as nimble fill-lighter for smart devices.

	<b>02T</b>	<b>02D</b>	<b>04C</b>
Color temp.	3200K	5600K	RGB
CRI	90ra		
Control	Dimming : 5% ~ 100%		
Battery	Li-Ion 3.7V		
Run time	2 hours		
Green-marenta	3M		

A specially-designed bracket for smart devices





AMS-50T/D is developed to replace conventional sun-gun light. The light is capable of lighting up more than 3,000 lumen in a small package.

# LED Genielite

## AMS-50T/D

	3200K	• • • • •	5600K	Others
Light source	High CRI LED (COB type) × 4EA (40W)			built-in 1/4" screw hole mount  optional parts : battery pack, tilting bracket, D-tab cable  barndoor included
Beam angle	140 °			
Color temp.	2900K ~ 5600K			
CRI	85ra		85ra	
Luminous flux	3400 lumen		3400 lumen	
Luminous intensity	1,200 lx @ 1m		1,200 lx @ 1m	
Driver	Flicker-Free by CC driver (efficiency > 93%)			
Control	Dimming (5% ~ 100%)			
Input voltage	12 ~ 24VDC			
Battery pack (opt.)	14.8V 2600mAh Li-Ion (gun type)			
	Weight : 400g			
Housing material	Aluminium 6061 T6 (Aircraft grade) Type III black HA			
Cooling	Fan cooling (Ultra silence : Max. 14dB)			
Dimension	80 × 76 × 117(L)mm			
	Weight : 360g			

