

COMPARISON WITH OTHER PANELS

- ▶ rainproof, shock resistant aluminum body
- ▶ 2x times more light output
- ▶ best quality Osram LED
- ▶ Universal AC&DC with Vlock or Gold mount
- ▶ more than bi-colour 2700K to 6500K
- ▶ thin, portable, easy to rig
- ▶ bi-directional DMX RDM
- ▶ modular design for multipanel
- ▶ affordable european made quality
- ▶ two years warranty. Made in Barcelona (Spain)



www.thelight.com.es

info@thelight.com.es

Intellectual Property

THELIGHT VELVET light technology is protected under
spanish patents and international patents pending

2015 © Copyright THELIGHT. All rights reserved.

the most robust & advanced LED panel

VELVET²
LIGHT



RAINPROOF

Rocky body 100% aluminum

SOFT LIGHT

Natural shadow-less light

POWERFUL

450 Lux at 3m / 10 ft

THELIGHT

the unique all-in-one Light



THELIGHT introduces **Rainproof VELVET LIGHT 1** the most robust and advanced LED panel producing velvety soft light



MADE TO LAST

Rainproof IP54

Robust 100% aluminum body made to endure the tougher working conditions on any location or studio

Best quality OSRAM LED

THELIGHT electronics and the aluminum heatsink keep the LED in the optimum temperature to last beyond 50.000 hours

NATURAL SOFT LIGHT

Incredibly soft and wraparound quality light to easily get beauty shots and natural portraits

MORE THAN BI-COLOR

VELVET is more than tungsten & daylight in the same unit: you can adjust color temperature from **2700K to 6500K**

AC/DC POWERED

VELVET is always ready to operate worldwide: using any battery from **12 to 35 VDC** with **Vlock or Gold battery mount** with universal **AC power 90-264 VAC**

QUALITY WHITE LIGHT

CRI>90 to get perfect skin tones and real colors with any HD or photo camera

Professional and consistent color rendition

Absolutely consistent lamp to lamp to mix as many units as you wish and get exactly the same light quality and color reproduction

QUICK SETUP

color temperature **instantly adjustable** from 2700K to 6500K dimmer smooth and flicker-free 0 to 100 with no color shift on-board control, digital display and **shock resistant buttons**

ADVANCED DMX RDM

DMX remote control even without a controller!

Master-slave function: link several units and operate without console. The Master will be the controller for the other units

Bi-directional DMX-RDM: perfect solution on studio simplifying the assignment and channel addressing of every fixture

ADVANTAGES

- ▶ Rainproof and shock resistant aluminum body
- ▶ More than bi-colour 2700K to 6500K digital
- ▶ Best quality Osram LED
- ▶ Natural shadowless light
- ▶ High output 450 Lux at 3m
- ▶ Worldwide AC & DC powered
- ▶ On-board and DMX control
- ▶ Thin, portable, easy to rig
- ▶ Modular design for multipanel
- ▶ Flicker free up to 3000 fps
- ▶ Silent fan-free operation
- ▶ 100% Made in Barcelona (Spain)



VELVET LIGHT 2 includes:

- ▶ 100% aluminum IP54 rainproof LED panel
- ▶ On-board and DMX digital control over:
 - ▶ Color temperature 2700K to 6500K
 - ▶ smooth Flicker-free dimming 0 to 100
- ▶ XLR-3 input for battery power 12-35VDC
- ▶ XLR-5 input connector for remote DMX control
- ▶ adjustable yoke with combined 28 / 16mm pin
- ▶ two years warranty

TECHNICAL SPECIFICATIONS

VELVET 2

COLOR TEMPERATURE	adjustable from 2700K to 6500K
LIGHT INTENSITY	dimnable 0 to 100 (smooth and flicker-free)
DIMENSIONS	670 x 308 x 68 mm
WEIGHT	6 Kg
POWER DRAW	150 W
POWER SUPPLY	12-35 V DC via XLR-3 Double Vlock or Gold mount battery plate 90-264V AC 50/60Hz
PHOTOMETRICS	3600 Lux / 334 fc at 1m / 3 feet 450 Lux / 42 fc at 3m / 10 feet
BEAM ANGLE	100°
LED RATED LIFE	more than 50.000 hours
COOLING	no noise, fan-free passive cooling
PROTECTION & CONSTRUCTION	rainproof IP54 rated, made of black anodized extruded aluminum and black powder coated sheet aluminum
VELVET LED TECHNOLOGY	OSRAM selected BIN LED + optic diffuser + CPU software control
QUICK MOUNTING ACCESSORIES	AC power supply, double Vlock or Gold adapter, foldable Snapgrid 40°, swivel-ball head, pole-op yoke, multipanel yokes, removable barndoors, DMX splitter cable, hard case, soft case



Specifications subjects to change without notice