

# Flexible Bi-color SMD LED Light



## S-2610

### 100W Flexible Bi-color SMD LED Light




- ◆ 504pcs ultra bright surface mounted LEDs
- ◆ Flexible 10°-360° lighting
- ◆ 100W power, 2400Lux @ 1 meter center
- ◆ 3000K-5600K continuously adjustable
- ◆ 0-100% flick-free dimming
- ◆ Super high CRI Ra≥97, TLCI≥97
- ◆ Separate controller with LCD touch screen
- ◆ 2.4G wireless cascading control
- ◆ Support DC / V-mount battery 11-17V input
- ◆ Water proof fabric for outdoor using
- ◆ Portable X bracket for lighting tripod mounting



## S-2620

### 50W Flexible Bi-color SMD LED Light

- ◆ 280pcs ultra bright surface mounted LEDs
- ◆ Flexible 10°-360° lighting
- ◆ 50W power, 1200Lux @ 1 meter center
- ◆ 3000K-5600K continuously adjustable
- ◆ 0-100% flick-free dimming
- ◆ Super high CRI Ra≥97, TLCI≥97
- ◆ Separate controller with LCD touch screen
- ◆ 2.4G wireless cascading control
- ◆ Support DC / V-mount battery 11-17V input
- ◆ Water proof fabric for outdoor using
- ◆ Portable X bracket for lighting tripod mounting



## Specifications

Model	S-2610	S-2620
LED	504pcs SMD LEDs	280pcs SMD LEDs
Luminance	2400Lux @ 1m	1200Lux @ 1m
Beam Angle	10°-360°	10°-360°
Color Temperature	3000K-5600K	3000K-5600K
CRI	Ra≥97	Ra≥97
TLCI	TLCI≥97	TLCI≥97
Input	100W	50W
Voltage	DC 11-17V	DC11V - 17V
Dimensions - light	600mm×460mm	455mm×315mm
Dimensions - controller	203mm×123mm×71mm	258mm×80mm×66mm
Weight	Light: 0.46Kg; Controller: 0.84Kg; AC adaptor: 0.43Kg	Light: 0.29Kg; Controller: 0.81Kg; AC adaptor: 0.29Kg